



Standard 24VDC KIT

KTP-CB609-T23 Series for FTP-609 Series

Product Specification

- | | | | |
|---|---|------------------------------|---------------|
| ● Board type | KTP-CB609-T23 | | |
| ● Printer type | FTP-629 Series | FTP-639Series | FTP-639MCL364 |
| ● Operating power | 24VDC | 24VDC | 24VDC |
| ● Current peak | approx. 3,0A | approx. 4,0A | approx. 5,6A |
| ● Paper insertion | rear | rear | rear |
| ● Paper width | 60mm | 80mm | 82,5mm |
| ● Eff. printing width | 54mm | 72mm | 80mm |
| ● Baud rate | 9.600 standard, max. 115.200 | 9.600 standard, max. 115.200 | |
| ● USB 1.1 | full speed | | |
| ● Print direction | portrait/landscape/upside down for all printer types | | |
| ● Character spacing | 20, 16, 14, 12 & 10x22 dots | | |
| ● Character addressing | 1 byte codepage, 2 byte Unicode | | |
| ● Character modification | enlarge, emphasise, underline, reverse, italic, sub- superscript | | |
| ● Standard font | Codepages 437, available 737, 850, 852, 857, 860, 866, 869, 1252, 1253, 1254 | | |
| ● Graphic mode | HP PCL5- line graphics | | |
| ● Label | graphics or text | | |
| ● Bar code | Code 2/5, Codebar, Code 39, Code 128, EAN 8/13/128, UPCA/E for all printer types | | |
| ● Memory | 448KB Flash for fonts, logo & download characters | | |
| ● Drivers | Windows 2K, XP, Linux CUPS or ASCII Mode with ESC/FS Commands for all printer types | | |
| ● Operating temp. | -20°C to +70°C | | |
| ● Storage temp. | -20°C to +85°C | | |
| ● Cutter function | full & partial cut | | |
| ● Printing speed | 200mm/sec. | | |
| ● Paper detection, head up detection, head temperature detection, label function possible | | | |
| ● Paper near end function, paper end function | | | |
| ● Online function for "printer status" | | | |
| ● Remarks: cable set is included in the delivery | | | |