



Standard Kiosk Thermal Printer Presto KTP-602 Series

Product Specification

● Printer type	KTP-622-*X	KTP-632-*X	KTP-642-100
● Operating power	24VDC	24VDC	24VDC
● Current peak	approx. 3,5A	approx. 3,5A	approx. 4,0A
● Paper insertion	rear	rear	rear
● Paper width	2 inch/60mm	3 inch/80mm	4 inch/112mm
● Eff. printing width	56mm	72mm	104mm
● Printing speed	up to 100mm/sec.	up to 80mm/sec.	up to 50mm/sec.
● Paper thickness	60-80ym	60-80ym	60-80ym
● Paper roll diameter	*X= 100/180/230mm	*X= 100/180mm	*X=100mm
● Operating temp.	-10°C to +40°C	-10°C to +40°C	-10 °C to +40°C
● Storage temp.	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C
● Head life	30km	30km	30km
● Head configuration	448dots/line	576dots/line	832dots/line
● Cutter life time	up to 500.000 cuts	up to 500.000 cuts	up to 250.000 cuts
● Cutting type	full or partial	full or partial	full or partial
● Interface	RS232 & USB	RS232 & USB	RS232 & USB
● Drivers:	Win98/2K/XP/CE, Linux, ASCII commands		
● Mech. dim. (WxDxH)	95x160x125mm	118x160x125mm	t.b.a.

- Paper auto feed detection, head up detection, black mark detection, head temperature detection
- Paper near end sensor, paper end sensor

Product Applications

- Kiosk
- ATM
- Ticketing
- Gaming
- Receipt