



2 Inch Panel Mount Thermal Printer PMTP-230

Product Specification

● Printer type	Fujitsu Thermal Printer
● Operating power	4,2-8,5VDC
● Current peak	approx. 2,4A
● Paper roll diameter	30mm
● Paper insertion	easy loading
● Paper width	57mm
● Eff. printing width	48mm
● Printing speed	50mm/sec.
● Paper thickness	60ym
● Operating temp.	-10°C to +60°C
● Storage temp.	-20°C to +60°C
● Head life	50km
● Head configuration	384dots/line
● Interface	RS232C
● Drivers	WIN95/98/2K/XP
● Bar code	type 39
● Baud rate	min. 9,6kBaud, max. 115,6kBaud (standard)
● Default font	16x32
● Fond set	code table 850
● Graphic mode	normal/compressed
● Mech. dim. (WxDxH)	82,3x77,4x38,5mm
● Customization	colour of plastic case and branding (logo)
● Paper detection, head up detection, head temperature detection	standard

Product Applications

- Mobile
- ECR/Cash
- Hand held
- Receipt
- Medical

itp systems & solutions GmbH & Co.KG
 Weiherweg 11, D-83533 Edling, Germany
 Phone: +49/(0)8071/5972460- Fax: +49/(0)8071/5972461; e-mail: info@itpsyso.com ; www.itpsyso.com

YOUR SUCCESS IS OUR MOTIVATION