



Fujitsu Heavy Duty Thermal Printer

FTP-601MCL101/102/301/302

FTP-601MCL201/202/351/352

Product Specification

● Printer type	FTP-601MCL101 /102	FTP-601MCL201 /202	FTP-601MCL301 /302	FTP-601MCL351 /352
● Operating power	24VDC	24VDC	24VDC	24VDC
● Current peak	approx. 3,5/5,2/6,0A	approx. 2,3/5,2A	approx. 3,5/5,2A	approx. 2,3/5,2A
● Paper insertion	front/rear	front/rear	front/rear	front/rear
● Paper width	60/85/114mm	60/82mm	60/85/114mm	60/82/114mm
● Eff. printing width	56/80/104mm	54/72mm	56/80mm	54/72mm
● Printing speed	100mm/sec.	100mm/sec.	100mm/sec.	100mm/sec.
● Paper thickness	60-150ym	60-150ym	60-150ym	60-150ym
● Operating temp.	0°C to +40°C	0°C to +40°C	0°C to +40°C	0°C to +40°C
● Storage temp.	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C
● Head life	50km	50km	50km	50km
● Head configuration	448/640/832dots/line	432/576dots/line	448/640dots/line	432/576dots/line
● Cutter life time	-	-	300 000 cuts	300 000 cuts
● Cutting type	-	-	Guillotine method, full or Partial cut	
● Paper auto feed detection, head up detection, head temperature detection				

Product Applications

- Kiosk
- ATM
- Ticketing
- Label
- Receipt