

FTP-607 Thermal Printer Series

Features

- High speed
- Compact size
- ELM
- ELM with cutter
- Multi featuring die-cast frame
- High resolution
- Mounting compatible to FTP-608



Applications

- Kiosk
- Medical equipment
- Label (scale, courier)
- Banking machines
- Measuring devices
- Receipts (POS, ECR)
- Ticket

GENERAL SPECIFICATION	
Printing method	Direct thermo
Printing resolution (dots/mm)	8
Printing pitch (mm)	0.125 (H) x 0.125 (V)
Printing speed (mm/sec)	100
Operating voltage	24 V
Sensor paper out	Photo interrupter
Sensor head-up	Micro-switch (gold plated)
Sensor head temperature	Thermistor
Option	Auto cutter

MECHANISMS									
Mechanisms	Paper thickness (mm/x)	Paper path	Dots/line	Print speed (mm/sec)	Cutter	Reliability (KM/ M. pulses)	Cutter life (kCuts)	Size W x D x H (mm)	Weight (gr)
FTP-627MCL103	58/100	Curly	384	100	No	50/100	-	70.2x33.0x15.5	41.5
FTP-627MCL053	58/100	Curly	384	100	No	50/100	-	83.5x35.7x15.5	49
FTP-627MCL054	58/100	Straight	384	100	No	50/100	-	83.5x35.7x15.5	49
FTP-627MCL401	58/100	Curly	432	100	Yes	50/100	500	81.2x42.2x21.8	97
FTP-627MCL411	58/100	Curly	384	200	Yes	100/100	1000	81.2x42.2x21.8	97
FTP-637MCL103	80/100	Curly	576	100	No	50/100	-	92.4x33.0x15.5	52
FTP-637MCL401	80/100	Curly	576	100	Yes	50/100	500	103.2x42.2x21.8	116
FTP-637MCL411	80/100	Curly	576	170	Yes	100/100	1000	103.2x42.2x21.8	116